



BLSHD72104E2-LM/1

1 SATA 4ch Analog HD DVR



Features:

- Support AHD-M series real-time encoding;
- Support VGA, HDMI HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Model:

BLSHD72104E2-LM/1

Interface:

Parameter:

	Model	BLSHD72104E2-LM/1
System	Main processor	Hi 3520D
Video	Video codec	H.264
	Encode	4*1080N/4*AHD-M
	Decode	1*1080N/1*AHD-M
	Multi-mode input	Pure Analog: 4*1080N;4*AHD-M;4*AHD-L Mixed: 2*720P(analog)+2*720P(network) Pure Network: 8*720P; 1*1080P; 4 *720P; 8*1080P;4*1080P
Audio	Audio compression	G.711A
	Intercom	support
Recording and Playback	Record mode	Manual>alarm>motion detection>timing
	Playback Channels	4 (pure local input mode)
Storage and backup	Space occupation	960H: 12~20G/ day*channel 720P: ~20G/ day*channel audio: 691.2M/ day*channel
	Backup mode	Network backup、USB HDD, USB writer、SATA writer
Interface	Video input	4 BNC
	Video output	1ch VGA,1ch HDMI
	Audio input	4ch RCA
	Audio output	1ch RCA
	Alarm input	No
	Alarm output	No
	Network interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	RS485:support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	1 SATA (Each maximum support 6T)
	Wireless	3G、WIFI(expand via USB)
Other	Power	12V/2A
	dimension	255mm(length)* 236mm(width)* 44mm(height)