



**BSNBFM15/1.0AHD**



**Parameter:**

<b>Model No.</b>	<b>BSNBFM15/1.0AHD</b>
<b>Video</b>	
CCD/CMOS	1/4 CMOS
Image Sensor	1045
DSP	8901
Horizontal Resolution	1.0Megapixel
Effective Pixels	1280(H)×720(V)
TV System	PAL/NTSC
Sync System	Internal
Usable Illumination	Color:0.01Lux@(F1.2,AGC ON),0 Lux with IR
S/N Ratio	≥55dB(AGC Off)
Video Output	1ch AHD high resolution output
<b>Lens</b>	
Focal Length	3.6mm
Lens Type	Fixed
<b>OPERATIONAL</b>	
DAY & NIGHT	Auto
ICR	YES
2DNR/3DNR	YES
Frame	1280×720@25 fps ; 1280×720@30 fps
Coaxial Cable Transmission Distance(3C/5C)	300M/500M
Twisted Cable Transmission (Cat 5.e standard)	300M
White Balance	Auto
Gama Correction	>R0.45
Electronic Shutter Speed	4/25s~1/45,000s
BLC	Auto
Gain Control	Auto
LED	φ 5 24PCS
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
IR Distance	15M
Power Consumption	<3W
Power Supply	DC12V ±10%
<b>MECHANICAL</b>	
Weatherproof Housing	IP66
Color/Material	white/aluminium alloy
Operation Temperature / Humidity	under 10°C ~ +50°C RH95% Max
Storage Temperature / Humidity	under 20°C ~ +60°C RH95% Max
Weight	0.45KG
Dimensions (W×H×D)	180.7×62×62mm