

K20



| Feature | |
|--------------|-----------------------|
| Users | 500/1000 Fingerprints |
| Transaction | 50,000 Logs |
| Card Storage | 1000 |
| Display | 2.8" color TFT |



PRODUCT HIGHLIGHTS

| Technical Specification | | |
|-------------------------|-----------------------|---|
| Storage Capacity | Fingerprint Templates | 500/1000 |
| | Transaction Storage | 50000 |
| | Card Capacity | 500 |
| | Card Reader | Yes |
| Biometric | Fingerprint Sensor | 500 DPI Optical Sensor |
| | FAR | <=0.0001% |
| | FRR | <=1% |
| | Identification speed | <=1 sec |
| | Algorithm Ver | 10 |
| Audio/Visual | Display | 2.8" Color TFT |
| | Keypad | 4 x 4 Keypad |
| | LED Indicator | Green/Red |
| | Schedule Bell/Speaker | Mini Speaker |
| Communication | Communication | TCP/IP, USB-host |
| | Push data | NA |
| | Standard features | Inbuilt Battery Backup,Self Service Query,SSR Recorder, |
| | | Automatic Status Switch,DST,T9 Input |
| Power & Environment | Power Supply | 5V DC, 0.8 Amps |
| | Operating Temperature | 0°C to 45°C |
| | Operating Humidity | 20% - 80% |
| | Dimension | 185 x 140 x 30 mm |



PRODUCT HIGHLIGHTS

| | | | |
|---------------------------|----------------------|---|--|
| Access Control | Wiegand | NO | |
| | Relay | 5V | |
| | Support Fire Alarm | NO | |
| | Door Sensor | NO | |
| | Anti Passback | NO | |
| | Door Bell | NO | |
| Exit Readers | Support exit readers | Push Button | |
| Optional | Battery | Yes | |
| | Card readers | NO | |
| | Communication | NA | |
| | Dual Mode | Either SSR Mode or Software Mode | |
| Compatibility | | | |
| Compatible Software & SDK | | Smart office suite desktop | |
| | | Etime track lite desktop | |
| Major Applications | | Time & Attendance, Canteen management, School attendance, | |
| | | Production Management, Gym & clubs | |