



## S990A





eature	
Special feature	Push Data Technology
Card Capacity	30,000
Transactions	1,00,000 Logs
CPU	32 bit Microprocessor - 800Mhz





## **PRODUCT HIGHLIGHTS**

Technical Specification		
Storage Capacity	Card Capacity	30,000
	Card Reader	Yes
	Transaction Storage	1,00,000
	CPU	32 bit High End Microprocessor - 800 MHz
Biometric	FAR	<=0.0001%
	FRR	<=1%
	Identification speed	<=0.1 sec
	Algorithm Ver	NA
Audio/Visual	Display	2.8" TFT
	Keypad	4 x 4 with 5 function Keys
	LED Indicator	Green/Red
	Schedule Bell/Speaker	Mini Speaker
Communication	Communication	RS232/485, TCP/IP
	Push data	Standard
	Standard features	Work Code,SMS,DLST, Self service query, Status Switch
Power & Environment	Power Supply	12V DC , 1.5Amp
	Operating Temperature	0°C to 45°C
	Operating Humidity	20% -80%
	Dimension	212 x 157 x 40 mm





## **PRODUCT HIGHLIGHTS**

Access Control	Wiegand	In & Out both 26 or 34 bit (With or without site code)
	Relay	12 V
	Support Fire Alarm	Yes
	Door Sensor	Yes
	Anti Passback	Yes
	Door Bell	Yes
Exit Readers	Support exit readers	KR500E / Exit Button, 101HE
Optional	Battery	Yes
	Card readers	Yes
	Communication	Wifi/GPRS
	Printer	Yes
Compatibility		Compatible with Multi Door controllers via weigand
		External Speaker output available (Optional)
		External Bulb output available (Optional)
Compatible Software & SDK		Smart office suite desktop and web
		etime track lite desktop & web
		SDK for desktop applications
		Web based Device Manager/ePush server using Push data. Helps developers & integrators
		Supports 3rd Party Payroll/HRMS/ERP and Other applications
Major Applications		Time & Attendance , Canteen management, School attedance,
		Production Management, Gym & clubs