

SC405

Active System





Feature	
Fingerprint Capacity	3000
Transactions	50,000 Logs
Sensor	500 DPI Optical Sensor
СРИ	400MHz



PRODUCT HIGHLIGHTS

ive System

Technical Specification		
Storage capacity	Fingerprints templates	3000
	Card Storage	3000
	Transaction storage	50,000 Logs
	Card reader	Yes
	СРИ	32bit Microprocessor
Biometric	Algorithm Ver	NO
	FAR	<=0.0001%
	FRR	<=1%
	Identification speed	<=0.5sec
Audio/Visual	Display	Color TFT
	Keypad	4 x 4 Keypad
	LED Indicator	Green/Red
	Schedule Bell/Speaker	Mini Speaker
Communication	Communication	RS232/485, TCP/IP
	Push data	No
	Standard features	DLST
Power & Environment	Power Supply	12V DC, 1.5A
	Operating Temperature	0°C - 45°C
	Operating Humidity	20% -80%
	Dimension	143 x 95.5 x39.5mm



PRODUCT HIGHLIGHTS

ive System

Access Control	Wiegand	In & Out
	Relay	Inbuilt relay to communicate with Locks, Alarms & Door Sensors
	Support Fire Alarm	Yes
	Door Sensor	Yes
	Anti Passback	Yes
	Door Bell	Yes
Exit Readers	Support exit readers	KR 500E / Exit Button / 101 HE,50 time zones, 5 groups, 10 time combinations
Optional	Battery	No
	Card readers	Yes
	Communication	No
	Sensor	Mifare
Compatibility		Compatible with Multi Door controllers via weigand
		External Speaker output available (Optional)
		External Bulb output available (Optional)
Compatible Software and SDK		Smart office suite desktop
		etime track lite desktop & web
		SDK for desktop applications
		Web based Device Manager/ePush server using Push data. Helps developers & integrators
		Supports 3rd Party Payroll/HRMS/ERP and Other applications
Major Applications		Time & Attendance , Canteen management, School attedance,
		Production Management, Gym & clubs