



X628





Feature		
Special Feature	Push Data Technology	
Fingerprint Capacity	3000 Templates	
ID Card Capacity	3000 Cards	
Transactions	1,00,000 Logs	







Tashuisal Cassification			i
Technical Specification	I	Ī	
Storage Capacity	Fingerprint Templates	3000	
	Card Capacity	3000	
	Transaction Storage	1,00,000	
	Card Reader	Yes	
	СРИ	800 MHz	
	Fingerprint Sensor	500 DPI Optical Sensor	ĺ
Biometric	FAR	<=0.0001%	
	FRR	<=1%	
	Identification Speed	<=0.5 sec	
	Algorithm Ver	10	
Audio/Visual	Display	2.8" TFT	
	Keypad	4 x 4 Keypad	
	LED Indicator	Green/Red	
	Schedule Bell/Speaker	Mini Speaker	
Communication	Communication	RS232, RS485, TCP/IP, USB	
	Push data	Standard	
	Standard features	Work Code,SMS,DLST, Self service query, Status Switch	
Power & Environment	Power Supply	5V DC, 2 A	
	Operating Temperature	0°C to 45°C	
	Operating Humidity	20% -80%	
	Dimension	190 x 135.8 x 51.5mm	
Access Control	Wiegand	NO	
	Relay	NO	
	Support Fire Alarm	NO	ĺ
	Door Sensor	NO	
	Anti Passback	NO	
	Door Bell	NO NO	
Exit Readers	Support exit readers	NO	
Optional	Battery	NO	
	Card readers	NO	
	Communication	NO	
	n	luo.	
a vil the	Printer	NO	
Compatibility		External Speaker output available (Optional)	
		External Bulb output available (Optional)	
Compatible Software & SDK		Smart office suite desktop and web	
•			
		etime track lite desktop & web	
		SDK for desktop applications	
	ļ	Web based Device Manager/ePush server using Push data.	
		.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
		Helps developers & integrators	
		Supports 3rd Party Payroll/HRMS/ERP and Other applications	
Major Applications		Time & Attendance , Canteen management, School attendance,	
		Production Management, Gym & clubs	