



K200





Feature	
Card Capacity	30,000
Transaction Capacity	50,000
СРИ	32 bit Microprocessor
Display	128 x 64 OIED with white Color





PRODUCT HIGHLIGHTS

Proximity Time and Attenda	nce System	
Storage Capacity	Card Capacity	30,000
	Transaction Storage	50,000
	Card Reader	NA
	Card Storage	NA
	СРИ	32 bit microprocessor
Biometric	Read range	8 - 10 cms
	FAR	<=0.0001%
	FRR	<=1%
	Identification speed	<=0.5 sec
	Algorithm Ver	10
Audio/Visual	Display	128 x 64 OIED with white Color
	Keypad	4 x 4 Keypad
	LED Indicator	Green/Red
	Schedule Bell/Speaker	Mini Speaker
Communication	Communication	RS232/485, TCP/IP
	Push data	NA
	Standard features	DLST
Power & Environment	Power Supply	5V DC, 400mA
	Operating Temperature	0 C to 45 C
	Operating Humidity	20% - 80%
	Dimension	90 x 190 x3.5 mm





PRODUCT HIGHLIGHTS

Access Control	Wiegand	NO
	Relay	NO
	Support Fire Alarm	NA
	Door Sensor	NA
	Anti Passback	NA
	Door Bell	NA
Exit Readers	Support exit readers	NA
Optional	Battery	NO
Compatibility		External Speaker output available (Optional)
		External Bulb output available (Optional)
		Compatible with Multi Door controllers via weigand
Compatible Software & SDK		Smart office suite desktop
		Etime track lite desktop
		SDK for desktop applications
		Web based Device Manager/ePush server using Push data
		Helps developers & integrators
		Supports 3rd Party Payroll/HRMS/ERP and Other applications
Major Applications		Time & Attendance , Canteen management, School attedance,
		Production Management, Gym & clubs