

InBio-460-Pro



Feature	
Fingerprint Capacity	3000
Log Events Capacity	100,000
Card holders Capacity	30,000
Communication	TCP/IP and RS-485

Special Features	
	Embedded Fingerprint verification and advance
	access control function
	It can be installed easily on your network also
	support TCP/IP and RS485 communication
	1/2/4 Door models can be mixed and matched in
	an optimised System Architecture
	Data is preserved if power is lost, Controller
	continues to operate if data connection is
	interrupted
	Anti-Passback, First-Card Opening, Multi-Card
	Opening
	Duress Password Entry, and Auxilary input/output
	linkages are inbuilt into controller firmware



PRODUCT HIGHLIGHTS

Technical Specification	
Number of doors controller	4 Door
Numbers of readers supported	12 (8 RS-485 Reader, 4 26-bit wiegand reader)
Types of readers supported	26-bit Wiegand & RS485 FR Series Reader
Number of Inputs	12(4 Exit Device, 4 Door Status, 4 AUX)
Number of Outputs	8 (4-Form C Relay or Lock & 4-Form C Relay for Aux Output)
Card holders Capacity	30,000
Fingerprint Capacity	3,000 (optional 20,000)
Log Events Capacity	1,00,000
Communication	TCP/IP and RS-485
Package Dimension	350(L)×90(H)×300(W)mm
Package Weight	3.7kg
CPU	32 bit 400MHz CPU