

ProRF-T



Features	
	Modern Design & Interactive UI
	Simple Management & Scalability
	Multiple Verification Modes: Finger Vein / Card / Password
	Touch Keypad
	Built In Camera: Event Snapshot and User Photo



PRODUCT HIGHLIGHTS

Technical Specification	
RFID Access Control System	
Card Capacity	50,000
Transactions Capacity	1,00,000
User Photos	3,000
Event Photos	7,000
Communication	TCP / IP, RS485 (For Slave Reader), USB Host, Wiegand Input / Output, Security Relay Box
Hardware	1.2GHz Dual Core CPU, Memory 128MB RAM / 256MB Flash, 2.4 Inches, TFT-LCD Touch Screen, 125KHz, EM Reader / Mifare (Optional), Hi-Fi Voice & Indicator, Tamper Switch Alarm Touch Keypad, 120° Wide Angle Camera
Standard Functions	Access Levels / Groups / Holidays, DST / Bell Schedule, Duress Mode (Password), Anti-Passback, Record Query, Custom Wallpaper & Screen Saver
Special Functions	Multiple Verification Modes Event Snapshot, User Photo(Optional)
Access Control Interface	Lock Relay Output, Alarm Output / Auxiliary Input, Exit Button / Door Sensor, Doorbell Output
Compatibility	Wiegand Slave Reader, BioSecurity Software RS485 Card Slave Reader (Optional)
Working Temperature	-10 °C ~ 50 °C
Dimensions	195.5 × 87 × 35 mm
Power	Operating Voltage 12V DC
Current Draw	< 500 mA