



H-B1-IR-2MP-AF

➔ IR Weatherproof Bullet IP Camera

Sensor : 1/2.7" 2.0M CMOS
Lux : 0.05Lux@F1.2 (Color Mode); 0.01
Lux@F1.2(B&W); 0Lux (IR on)
WDR Range : 96dB
SN Ratio : ≥ 41 dB (AGC OFF)
AGC : AUTO/MANUAL
WB : AUTO, INDOOR, OUTDOOR, sodium lamp
Mode, MANUAL
Noise Reduction : 2DNR, 3DNR
Exposure Mode : Program mode
(customizable shutter interval),
shutter mode (1/5 - 1 / 20,000s), slow shutter mode
Compression : H.264 Main profile / M-JPEG
Max Pixel : 1920x1080@60fps
Output Rate : Constant Bit Rate (CBR) or variable
bit rate (VBR), stream settable
range: 32Kbps ~ 10Mbps
Number of Visits : Main stream 3 users, sub
stream 6 users

Network protocol : TCP/IP, HTTP, NTP, IGMP,
DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS,
DNS, HTTPS, P2P
ONVIF protocol : ONVIF2.4
Compatibility : Support 3rd Party
Mobile Remote : Android, IOS
Internet Port : 1 port 10 / 100Base T Ethernet,
RJ45 port
Power : 12V DC, 2A
Working Temperature : -20°C to 60°C
Working Humidity : 0% to 90% RH (non-condensing)

Features:

- ▶ Varifocal Motorized Lens IR Bullet Camera
- ▶ 1/2.7" 1080P Sensor
- ▶ IR LED : 42PCS
- ▶ 2.8 - 12mm Autofocus Motorized Lens