



MD450

➔ Mini Dome IP Camera

Camera Performance

Image Sensor : 1/3.2" CMOS sensor
Resolution : 1280 x 720
Camera Lens : 4mm / 6mm fixed lens
Minimum Illumination : 0.1Lux (color), 0 Lux (B&W)
Built-in microphone
Day/Night : Software Switch

Video Coding

Main Processor : Hi3512
Operation System : Built-in Linux
Video Compression : H.264 main profile level 3
Audio Compression : G.726/G.711
Video Resolution : Main stream: 1280 x 720 ,
Secondary stream: 320 x 240
Video Frame Rate : 1~25 frame optional
Video Parameter : Brightness, contrast, saturation,
adjustable

Function Interface

Audio Input : Built-in Microphone
Audio Output : N/A
Alarm Input : N/A
Alarm Output : N/A
Motion Detection : 4 independent detection areas settable
Control Interface : N/A
Storage : Support local TF card to store video and snap,
up to 16G
Network Interface : 10Base-T/100Base-TX Ethernet
interface wireless WiFi (optional)
Protocol : TCP/IP, HTTP, TCP, UDP, ARP, SMTP, FTP,
DHCP, DNS, DDNS, NTP, UPNP, RTSP

Work Environment

Power supply : 12V DC 1.5A
PoE: 802.3af PoE standard (optional)
Power consumption : 8W max
Working Temperature : -20°C ~ 55°C
Working Humidity : 10% ~ 95% RH