



MD470

➔ Mini Dome IP Camera

Camera Performance

Image Sensor : 1/3.2" megapixel WDR progressive CMOS
Resolution : 1280 x 720
Camera Lens : 6 mm fixed lens
Minimum Illumination : 0.1Lux (color), 0 Lux (B&W)
Built-in microphone

Video Coding

Main Processor : Hi3512
Operation System : Built-in Linux
Video Compression : H.264 main profile level 3
Audio Compression : G.726/G.711
Video Resolution : Main stream: 1280 x 720 ,
Secondary stream: 320 x 240
Video Frame Rate : NTSC : 1-30 frames,
PAL : 1-25 frame optional
Video Parameter : Brightness, contrast, saturation
adjustable

Function Interface

Audio Input : Built-in Microphone
Audio Output : N/A
Alarm Input : N/A
Alarm Output : N/A
Motion Detection : 4 independent detection areas
Control Interface : N/A
Storage : Support local TF card to store video and
snap, up to 32G
Network Interface : 10Base-T/100Base-TX Ethernet ;
WiFi 802.11 b/g/n wireless network (optional)
Protocol : TCP/IP, HTTP, TCP, UDP, ARP, SMTP,
FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP

Work Environment

Power supply : 12V DC 1.5A
PoE: 802.3af PoE standard (optional)
Power consumption : 8W max
Working temperature : -10°C ~ 55°C
Working Humidity : 10% ~ 95% RH