



## IP350

### ➔ Megapixel Fixed Box IP Camera

#### Camera Performance

Sensor : 1/3.2" CMOS sensor

Lens : 4-9mm varifocal lens

Minimum illumination : 0.1 Lux

Day/Night : N/A

#### Video Coding

Main processor : Hi3512

Operation system : Built-in Linux

Video compression : H.264 main profile level 3

Audio compression : G.726/G.711

Resolution : Main stream: 1280 x 720

Secondary stream: 320 x 240

Frame rate : 1~25 frame settable

Video parameter : Brightness, contrast, saturation, color adjustable

#### Work Environment

Power supply : 12V DC 1.5A

PoE: 802.3af PoE standard (optional)

Power consumption : 8W max

Work temperature : -10°C ~ 55°C

Work humidity : 10~95 % RH

#### Function Interface

Audio streaming : Two way

Audio input : 1 channel line/Mic input

Audio output : 1 channel line output

Alarm input : 1 channel on/off input ( NO/NC settable)

Alarm output : 1 channel on/off alarm output, external max working voltage 120V AC 1A/24V DC 1A

Motion detection : 4 independent detection areas settable

Control interface : 1 RS-485 interface

Storage : Support SD card upto 32GB for video and snapshots

Network interface : 10Base-T/100Base-TX Ethernet interface

WIFI 802.11b/g/n wireless network (optional)

Protocol : TCP/IP, HTTP, TCP, UDP, ARP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP, RTP