



X-NVR-32-4S

➔ 32 Channel NVR

System : Processor : Embedded Processor

System : Embedded Linux

Video : Video Input : 24ch5M/32ch4M/16ch1080P

Playback : 4ch5M/9ch4M/16ch1080P

Decode : H.265/H.264

Audio : Compression : G.711a

Intercom : Unsupport

Management : Record Mode : Manual>Alarm>

Motion detection>Timing

Inquire Mode : Inquire by Time/

Calendar/Event/Channel

Storage Mode : HDD Storage, Network Storage

Backup : Network, USB, SATA

Interface : HDMI Output : 1 x HDMI (MAX:4K)

VGA Output : 1 x VGA (MAX:1080P)

Ethernet port : 1 x RJ45 1 x 10/100/1000Mbps

Ethernet port,

POE ports : N/A

Alarm I/O : 1/1

Alarm I/O : 16/4

USB Port : 2 x USB2.0 ports, 1 x USB3.0 ports

HDD : 4 x SATA interface (Up to 24TB)

General : Temperature : 0°C - + 55°C

Humidity : 10% - 90% RH

Power Supply : 12V/6A

Consumption : <10W (Without HDD)

Weight : Around 1.6KG

Dimension : 440mm(L) x 400.5mm(W) x 60mm(H)