

ML-10



Features

Capacitive sensing technology - Touch to open

Independent clutch motor design under patent protection

Idle handle design to prevent from forcible entry

Handle, latch and strike is reverse design for all door open direction

Support passage mode - Normal Open

Ease to install, Program & use - No wiring is required



PRODUCT HIGHLIGHTS

Technical Specification		
Storage Capacity	Material	Zinc Alloy
	Mortise	American standard single latch
Dimensions	Front	69(W)×155(L)×35(D)mm
	Back	69(W)×155(L)×25(D)mm
Storage Capacity	Fingerprint Sensor	500 DPI Optical Sensor
	User Capacity	90
	Fingerprint	90
User Capacity	Admin	10
	Normal User	60
	Temporary User	20
	Identification Speed	≤ 1.5 sec
	FAR	≤ 0.0001%
	FRR	≤ 1%
Environment	Operating Temperature	- 20°C - 55°C
	Power input	4 x 1.5v AA alkaline Battery
	Backup unlock mechanism	Emergency battery
		Mechanical key
LED Indicator	Red	Fail
	Green	Successful
Door Thickness	Standard	39 to 46mm
		47 to 54mm
	Optional	30 to 38mm
		55 to 60mm
	Backset	60mm or 70mm (adjustable)