

32CH 1.5U Network Video Recorder

Key Features

- Up to 32 channel IP camera input
- H.264/MJPEG dual codec decoding
- Max 200Mbps incoming bandwidth
- Up to 5MP resolution preview&playback
- HDMI/VGA/TV simultaneous video output
- 8/16 channel synchronous realtime playback, GRID interface
- Support Multi-brand network cameras: Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP PLUS, Honeywell, Dahua, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek etc.
- ONVIF Version 2.4 conformance
- 3D intelligent positioning with PTZ camera
- Support 4 SATA HDDs up to 16TB, 1 eSATA port, 2 USB(1 USB3.0)
- Multiple network monitoring: Web viewer, CMS(PVMS) & Smart Phone(PMOB)



Technical Specifications

Model	PI-NL2432K
System	
Main Processor	Dual -core embedded processor
Operating System	Embedded LINUX
Video & Audio	
IP Camera Input	32 channel
Two-way Talk	1channel Input, 1channel Output, RCA
Display	
Interface	1 HDMI, 1 VGA, 1 TV
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
Display Split	1/4/8/9/16
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Recording	
Compression	H.264/MJPEG
Resolution	5MP (2560×1920) /3MP (2048×1536) /1080P(1920×1080) / 720P(1280×720) / D1 (704×576/704×480)&etc.
Record Rate	200Mbps
Bit Rate	48 ~ 8192kbps
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1-120 min (default: 60 min), Pre-record: 1-30 sec, Post-record: 10-300 sec
Video Detection & Alarm	
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank
Alarm Input	16 channel
Relay Output	4 channel
Playback & Backup	
Sync Playback	1/4/8/16
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device/Network/Internal SATA burner/eSATA Device
Network	
Ethernet	1 RJ-45 port (10/100/1000Mbps)
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android
Storage	
Internal HDD	4 SATA ports, up to 16TB
External HDD	1 eSATA port
Auxiliary Interface	
USB	2 ports (1 Rear USB3.0, 1 Front USB2.0)
RS232	1 port, For PC communication & Keyboard
RS485	1 port, For PTZ control
General	
Power Supply	AC 100V-240V/50/60HZ
Power Consumption	40W(without HDD)
Working Environment	-10°C ~+55°C / 10%-90%RH / 86-106kpa
Dimension (W×D×H)	1.5U, 440mm×413mm×75mm
Weight	6KG(without HDD)