



ML10-ID

ML10-ID is integrated with fingerprint recognition,RFID card technology and optional BLT 4.0 technology, which enables you to unlock the door and manage users through your mobile phone.

Features

- Bluetooth connection (optional)
- Four independent unlock methods: Fingerprint, ID-tag, mechanical key, and mobile phone (optional)
- User capacity: 180
- Fingerprint capacity: 90
- Card capacity: 90
- Rugged, sleek and compact design
- American standard single latch for easy replacement and installation
- Independent clutch motor design under patent protection
- Idle handle design to prevent possible entries
- Registration data are stored even if there is power loss
- Handle, latch and strike is reversible design for all door open direction
- Capacitive sensing technology - Touch to open
- Emergency key override (concealed)
- LED indicator and inbuilt buzzer
- External terminals to draw back-up power from a 9V battery
- Low battery warning
- Normal Open mode
- Easy to program and easy to use
- Easy to install—no wiring required
- 3 user groups - Admin, Normal User and Temporary User
- Backset is 60 mm or 70mm (adjustable)
- German standard mortise with one latch and one deadbolt (optional)

Specifications

Material	Zinc Alloy
User Capacity	Admin -20 Normal User -120 Temporary User - 40
Operating Temperature	-20°C - 55°C
Power Supply	4xAA Alkaline Battery
Backup Unlocking Way	Mechanical Key & 9V Battery
Door Thickness	30-38 mm (optional) 39-46 mm (standard) 47-54 mm (standard) 55-60 mm (optional)
Dimensions	Front - 69(W)×155(L)×35(D) mm Back - 69(W)×155(L)×25(D) mm

