

AT-2013L10-M



Main Features

- ⇒ 1/3" 1.3MP Progressive scan CMOS
- ⇒ Powerful 20x Optical Zoom
- ⇒ Third Generation Infrared Technology
- ⇒ Up to 256 Presets, 16 patrol, 16 Pattern
- ⇒ Max 240°/s pan speed, 360° endless pan rotation
- ⇒ IR Range of 100 Mtr., IP66
- ⇒ Mobile Software for Android, iOS
- ⇒ CMS Software: IVMS



SPECIFICATION - AT-2013L10-M

| MODEL | AT-2013L10-M |
|-------------------------|--|
| Image Sensor | 1/3" 1.3MP Progressive scan CMOS |
| Effective Pixels | 2688(H)x920(V) |
| Video Output | BNC(1.0Vp-p/75Ω), PAL / NTSC |
| White Balance | Auto/Manual |
| S/N Ratio | more than52dB |
| Minimum Illumination | Color: 0.03 lux (F1.6, 50IRE), B/W: 0.01 lux (F1.6, 50IRE) |
| Focal Length | 4.7mm~94mm |
| Focus Control | Auto / Manual |
| Angle of View | H: 59.7° ~ 3.8° |
| Iris Control | Auto/Manual; F1.6 ~ F3.3 |
| Electronic Shutter | Auto/Manual; shutter time: 1/15 s ~ 1/10000 s |
| Agc | Auto/Manual |
| Optical Zoom | 20x |
| Digital Zoom | Supports |
| Pan Travel | 360° endless, Pan Speed: 0.1°/s ~ 240°/s |
| Tilt Travel | -15° ~ 90°, Tilt Speed: 0.1° ~160°/sec |
| Preset | 256 |
| Preset speed | Pan: 300° /s; Tilt: 240° /s |
| Special Features | IR Range upto 100m, Up to 256 Presets, 16 Patrol, 16 Pattern |
| privacy masking | up to 8 areas |
| Day/Night:IR Cut Filter | IR-cut filter with auto switch (ICR) |
| Video Compression | H.264 / MJPEG |
| Video Streaming | 1.3M(1 ~ 25/30fps) Triple Stream |
| Audio Comprerssion | G.711a |
| Audio Streaming | Two way Talk Supported |
| Protocol | L2TP,IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,PPPoE,RTP,RTSP, NTP,FTP,HTTP,SNMP,SIP |
| Operating Temperature | -40°C ~ +65°C (-40°F ~ 149°F), Humidity ≤ 90% RH(non-condensing) |
| Weatherproof Standard | IP66 |
| Weight | 5.28kg |