

AT-B20-MD



Main Features

- ⇒ 1/2.8" 2MP PS Max 25fps@1080P
- ⇒ Max 25fps@1080P
- ⇒ H.264 and MJPEG Triple-stream encoding
- ⇒ WDR, Day/Night(ICR), 2D/3D-DNR, AWB, AGC, BLC
- ⇒ C/CS Mount lens, Micro SD
- ⇒ 6 KV surge protection designed for network interface
- ⇒ Mobile Software for Android, iOS
- ⇒ CMS Software: IVMS



SPECIFICATION - AT-B20-MD

MODEL	AT-B20-MD
Image Sensor	1/2.8" 2MP PS CMOS Image Sensor
Minimum Illumination	Colour: 0.02 Lux (F1.2, 50IRE), Black & White: 0.008 Lux (F1.2, 50IRE)
Shutter Speed	Auto/Manual, 1/6s~1/8000s
White Balance	Auto/Manual
Lens	C/CS Mount Lens
Lens	C/CS Mount Lens
Agc	Auto/Manual
BLC	BLC/HLC/WDR(120db)
S/N Ratio	>50dB
Resolution	3MP/1080P/720P/VGA/QVGA
Video Streaming	Tripple
Video Compression	H.264/MJPEG
Motion Detection	Up to 2 areas
Privacy Mask	Up to 4 areas
ICR	IR-cut filter with auto switch (ICR)
Audio Input	impedance 35 k Ω ; amplitude 2 V [p-p]
Audio Output	impedance 600 Ω ; amplitude 2 V [p-p]
Audio Compression	G.711
Alarm IN	2 IN
Alarm Out	1 Out
WDR	UP to 120db
Interface	1 RS485 (support Pelco-D/P)
Protocol	IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,RTP,RTSP,Qos,DNS,DDNS,NT P,FTP,UPnP,HTTP, Onvif
Ethernet	10M/100M Base-TX Ethernet
OSD	UP TO 8OSDS
Operating Temperature	-20°C ~ +60°C (-4°F ~ 140°F)
Humidity	≤ 90% RH(non-condensing)
Power Source	24 V AC, 12 V DC, or PoE (IEEE802.3 af)
Power Consumption	Power consumption: 4.8 W (6.8W with ICR on)
Weatherproof Standard	IP66
Dimension	151.5 x 71 x 65 mm (6.0" x 2.8" x 2.6") (excluding the lens)
Weight	0.48kg