

AT-T40FR3-MD



Main Features

- ⇒ 1/3" 4MP PS CMOS Image Sensor
- ⇒ Max 20fps@4MP
- ⇒ H.264 and MJPEG Triple-stream encoding
- ⇒ WDR, Day/Night(ICR), 2D/3D-DNR, AWB, AGC, BLC
- ⇒ 2.8~12mm Varifocal Lens
- ⇒ IR Range of 30 Mtrs, Micro SD, IP66, IK10, PoE
- ⇒ Mobile Software for Android, iOS
- ⇒ CMS Software: IVMS



SPECIFICATION - AT-T40FR3-MD

MODEL	AT-T40FR3-MD
Image Sensor	1/3" 4MP PS CMOS Image Sensor
Minimum Illumination	Colour: 0.06 Lux (F1.4, 50IRE), 0 Lux with IR on
Shutter Speed	Auto/Manual, 1/6s~1/8000s
White Balance	Auto/Manual
Lens	2.8~12mm Varifocal Lens
Agc	Auto/Manual
Video Compression	H.264/MJPEG
S/N Ratio	>55dB
Video Streaming	Tripple
Resolution	4MP@20fps
Frame Rate	4MP(2592x1520):Max.20fps,4MP(2560x1440):Max.25fps,3MP(2048x1520):Max.30fps;1080P(1920x1080)max.30 fps
Privacy Mask	Up to 4 areas
ICR	IR-cut filter with auto switch (ICR)
WDR	Digital
Protocol	IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,RTP,RTSP,Qos,DNS,DDNS,NT P,FTP,UPnP,HTTP, Onvif
Ethernet	1 RJ45 10M/100M Base-TX Ethernet
OSD	UP TO 8 OSDS
IR	IR range of 30 Mtr
Micro SD	Upto 120gb
Operating Temperature	-35°C ~ +60°C (-31°F ~ 140°F)
Humidity	≤ 90% RH(non-condensing)
Power Source	12 V DC or PoE (IEEE802.3 af)
Power Consumption	Max.9w
Weatherproof Standard	IP66
Dimension	253.4 ×86 ×71.7 mm (9.98" × 3.4" × 2.8")
Weight	0.93kg