

AT-S1000/1 MEDIA CONVERTER



Main Features:

- Fiber Port:single mode single fiber
- Distance:0-25KM
- Power-in:AC110V-AC220V/0.25A
- Port Out 5V
- Transmission Mode:10/100M full/half duplex
- Data buffer 1MBits
- Fast Ethernet

Specification:

Model	AT-S1000/1	
Items	10/100M multimode media converter	10/100M multimode media converter
Cable Type	Multimode fiber optics/ twisted pair	Multimode fiber optics/ twisted pair
Transmission Type	Fast Ethernet	Fast Ethernet
Transmission Mode	10/100M Full/half duplex	10/100M Full/half duplex
MTBF	>3years	>3years
BER	<1E-8	<1E-8
Data Buffer	1MBits	1MBits
Power Stability Factor	0.2° mW/c	0.2° mW/c
Input Power Range(dbm)	0~30v	0~40v
Operation Temperature	0°c~70°c	0°c~70°c
Storage Temperature	-45°c~80°c	-45°c~80°c
Maximum Current	800mA	800mA
Compatibility	Compatible with other brand Products	Compatible with other brand Products
EMC	According to FCC part15	According to FCC part15
Volume	95X70X26mm	External: L X W X H
	140X110X30mm	Internal: L X W X H