



## AT-208T2



### Main Features

- ⇒ 8 Ch. with 1080p Real time Live View
- ⇒ H.264/MJPEG dual codec decoding
- ⇒ 64/96 Mbps Incoming/Outgoing Bandwidth
- ⇒ Support 2 SATA HDDs up to 12TB, 2 USB
- ⇒ Support Multi-brand network cameras
- ⇒ Mobile Software for Android, iOS
- ⇒ CMS Software: IVMS



## SPECIFICATION - AT-208T2

<b>MODEL</b>	<b>AT-208T2</b>
Processor	Dual-core embedded processor
Operating System	Embedded LINUX
IP Camera Input	8 channel
Two-way Talk	1 channel, RCA
User Interface	GUI
Video Output	HDMI, VGA
Video Compression	H.264 / MJPEG
Video Resolution	up to 6MP
Video Recording	Max 96Mbps
Video Display Split	1/4/8/9
Audio Input	1 channel, RCA
Audio Output	1 channel, RCA
Hard Disk	2 SATA ports, up to 12TB
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Interface port	1 USB2.0, 1 USB3.0, 1 HDMI, 1VGA, 1 RJ45
Ethernet	1 RJ-45 10M/100M adaptive Ethernet Interfaces
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
power supply	12 VDC, 2A
Power consumption	≤6 W (without hard disk)
Working Temp	-10C°~+55C°(+14F°~+131°F)
Working Humidity	10%-90%
Dimension	360.0 ×254.3 × 43.6 mm (14.17" × 10.01" × 1.72")
Weight	≤1.42KG