



## AT-216T4



### Main Features

- ⇒ 16 Ch. with 1080p Real time Live View
- ⇒ H.264/MJPEG dual codec decoding
- ⇒ 128/96 Mbps Incoming/Outgoing Bandwidth
- ⇒ Support 4 SATA HDDs up to 12TB, 3 USB
- ⇒ Support Multi-brand network cameras
- ⇒ Mobile Software for Android, iOS
- ⇒ CMS Software: IVMS



## SPECIFICATION - AT-216T4

| <b>MODEL</b>        | <b>AT-216T4</b>   |
|---------------------|---|
| Processor           | Dual-core embedded processor  |
| Operating System    | Embedded LINUX  |
| IP Camera Input     | 16 channel  |
| Two-way Talk        | 1 channel, RCA  |
| User Interface      | GUI   |
| Video Output        | HDMI, VGA   |
| Video Compression   | H.264 / MJPEG   |
| Video Resolution    | up to 8MP   |
| Video Recording     | Max 96Mbps  |
| Video Display Split | 1/4/8/9/16  |
| Audio Input         | 1 channel, RCA  |
| Audio Output        | 1 channel, RCA  |
| Hard Disk           | 4 SATA ports, up to 12TB  |
| Playback            | Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom |
| Interface port      | 2 USB2.0, 1 USB3.0, 1 HDMI, 1VGA, 1 RJ45  |
| Ethernet            | 2 RJ-45 10M/100M adaptive Ethernet Interfaces   |
| Protocols           | HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS,IP Filter, PPPOE, DDNS, FTP, IP Server, P2P   |
| power supply        | 12 VDC, 2A  |
| Power consumption   | ≤6 W (without hard disk)  |
| Working Temp        | -10C°~+55C°(+14F°~+131°F)   |
| Working Humidity    | 10%-90%   |
| Dimension           | 44.0mm x 440.0mm x341.0mm (1.73" x 17.30" x 13.47")   |
| Weight              | ≤3KG  |