



## AT-232T8



### Main Features

- ⇒ 32 Ch. with 1080p Realtime Live View
- ⇒ H.264/MJPEG dual codec decoding
- ⇒ 200/96 Mbps Incoming/Outgoing Bandwidth
- ⇒ Up to 256 Presets, 16 patrol, 16 Pattern
- ⇒ Support 8 SATA HDDs up to 48TB, 3 USB
- ⇒ Support Multi-brand network cameras
- ⇒ Mobile Software for Android, iOS
- ⇒ CMS Software: IVMS



## SPECIFICATION - AT-232T8

<b>MODEL</b>	<b>AT-232T8</b>
Processor	Dual-core embedded processor
Operating System	Embedded LINUX
IP Camera Input	32 channel
Two-way Talk	1 channel, RCA
User Interface	GUI
Video Output	HDMI, VGA
Video Compression	H.264 / MJPEG
Video Resolution	up to 8MP
Video Recording	Max 96Mbps
Video Display Split	1/4/8/9/16
Audio Input	1 channel, RCA
Audio Output	1 channel, RCA
Alarm Input	8 channel
Alarm Output	2 channel
Hard Disk	8 SATA ports, up to 48 TB
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Interface port	1 USB2.0, 1 USB3.0, 1 HDMI, 1VGA, 1 RJ45, 1 RS485
Ethernet	2 RJ-45 10M/100M adaptive Ethernet Interfaces
Protocols	HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS,IP Filter, PPPOE, DDNS, FTP, IP Server, P2P
power supply	100 ~ 240 VAC
Power consumption	≤15 W (without hard disk)
Working Temp	-10C°~+55C°(+14F°~+131°F)
Working Humidity	10%-90%
Dimension	86.1mm x 442.0mm x421.0mm (3.39" x 17.40" x 16.57")
Weight	≤5.2KG