

AT-4K3164



Main Features

- ⇒ 16 Channel IP Camera Input
- ⇒ H.265/H.264 dual Video Formats
- ⇒ 160/320 Mbps Incoming/Outgoing Bandwidth
- ⇒ Upto 8 MP Recording Resolution
- ⇒ Support 4 SATA HDDs up to 24TB, 3 USB
- ⇒ Support Multi-brand network cameras
- ⇒ Mobile Software for Android, iOS
- ⇒ CMS Software: IVMS



SPECIFICATION - AT-4K3164

| MODEL | AT-4K3164 |
|---------------------|--|
| Processor | Dual-core embedded processor |
| Operating System | Embedded LINUX |
| Two-way Talk | 1 channel, RCA |
| IP Camera Input | 16 channel |
| User Interface | GUI |
| Video Output | HDMI, VGA |
| Video Compression | H.265 / H.264 |
| Video Resolution | UPTO 8MP |
| Video Recording | 160Mbps |
| Video Display Split | 1/4/8/9/16/32 |
| Audio Input | 1 channel, RCA |
| Audio Output | 1 channel, RCA |
| Alarm Input | 16 channel |
| Alarm Output | 4 channel |
| Hard Disk | 4 SATA ports, up to 24 TB |
| Playback | 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF |
| Interface port | 3 USB, 1 RS485, 2 RJ45 |
| Ethernet | 2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interfaces |
| Protocols | HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Server, P2P |
| Remote User | 128 |
| power supply | 100~240VAC |
| Power consumption | ≤ 12 W |
| Working Temp | -10C°~+55C°(+14F°~+131°F) |
| Working Humidity | 10%-90% |
| Dimension | 44MM x 440 mm x 344MM |
| Weight | ≤3.14kg |