



AT-4K3648



Main Features

- ⇒ 4 Ch. with 1080p Real time Live View
- ⇒ H.264/MJPEG dual codec decoding
- ⇒ 32/96 Mbps Incoming/Outgoing Bandwidth
- ⇒ Support 1 SATA HDDs up to 6TB, 2 USB2.0
- ⇒ Support Multi-brand network cameras
- ⇒ Mobile Software for Android, iOS
- ⇒ CMS Software: IVMS



SPECIFICATION - AT-4K3648

MODEL	AT-4K3648
Processor	Dual-core embedded processor
Operating System	Embedded LINUX
Two-way Talk	1 channel, RCA
IP Camera Input	64 channel
User Interface	GUI
Video Output	HDMI, VGA
Video Compression	H.265 / H.264
Video Resolution	8MP
Video Recording	320Mbps
Video Display Split	1/4/8/9/16/32
Audio Input	1 channel, RCA
Audio Output	1 channel, RCA
Alarm Input	16 channel
Alarm Output	4 channel
Hard Disk	8 SATA ports, up to 24 TB
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Interface port	3 USB, 1 RS485, 2 RJ45
Ethernet	2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interfaces
Protocols	HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Server, P2P
power supply	100~240VAC
Power consumption	≤ 20 W
Working Temp	-10C°~+55C°(+14F°~+131°F)
Working Humidity	10%-90%
Dimension	86MM x 442 mm x 425MM
Weight	≤5.13kg