



AT-4K3R648



Main Features

- ⇒ 64 Ch. with 1080p Real time Live View
- ⇒ H.265/H.264 dual Video Formats
- ⇒ 320 Mbps Incoming/Outgoing Bandwidth
- ⇒ Support 8 SATA HDDs up to 48TB, 3 USB
- ⇒ Support Multi-brand network cameras
- ⇒ Mobile Software for Android, iOS
- ⇒ CMS Software: IVMS



SPECIFICATION - AT-4K3R648

MODEL	AT-4K3R648
Processor	Dual-core embedded processor
Operating System	Embedded LINUX
Two-way Talk	1 channel, RCA
IP Camera Input	64 channel
User Interface	GUI
Video Output	HDMI, VGA
Video Compression	H.265 / H.264
Video Resolution	UPTO 8MP
Video Recording	320Mbps
Video Display Split	1/4/8/9/16/32
Audio Input	1 channel, RCA
Audio Output	1 channel, RCA
Alarm Input	16 channel
Alarm Output	4 channel
Hard Disk	8 SATA ports, up to 48 TBs
Playback	16 Channel
Interface port	3 USB, 1 RS485, 2 RJ45
Ethernet	2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interfaces
Protocols	HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Server, P2P
Remote User	128
power supply	100~240VAC
Power consumption	≤20w
Working Temp	-10C°~+55C°(+14F°~+131°F)
Working Humidity	10%-90%
Dimension	86MM x 442 mm x 531MM
Weight	≤5.13kg