

# CP- TNW-HP24G2F1-30

## 24 Ports PoE Switch



### Main Features

- Provide 24x 100Mbps downlink PoE Ethernet ports, 2x gigabit uplink Ethernet ports and 1x gigabit Fiber port
- Downlink Ethernet ports support PoE , each port supports max. 30W output
- Support power consumption indication( LED indicates power output status)
- Accord with IEEE802.3 , IEEE802.3u , IEEE802.3ab , IEEE802.3af/at standard
- 4K MAC address,2.75Mb cache

# CP- TNW-HP24G2F1-30

## 24 Ports PoE Switch

Feature	Specification
Downlink Ports	24x10/ 100Base- TX PoE+ , Link:16x Green LED PoE:16x Yellow LED
Uplink Ports	2x10/100/1000Base-T+1 x 1000Base-X(combo) , 2x Green LED
Network Standard	IEEE 802.3,IEEE 802.3u,IEEE 802.3 ab, IEEE 802.3z
Exchange Capacity	8.8Gbps
Transmission Distance	100m(Max.)
Data Package Cache	2. 75Mb
MAC Address List	4K
PoE Power Supply	End- span(1/ 2, 3/ 6),IEEE802. 3 af/ at
PoE Output	270W , 5x LED (Including 3x Green, 1x Yellow, 1x Red), separately indicate 30% , 60% , 90% , 95%~100%
PoE Power Budget	300W
CCTV Mode	Downlink ports only communicate with uplink ports , Restrain network storm under 2Mbps , Extend transmission distance to 250m , Rate:10Mbps(Downlink Ports)
Surge Immunity	6KV, Per: IEC61000- 4- 5
ESD Protection	6KV/8KV, Per:IEC61000-4-2
Power Input	1xAC Female Terminal , Mains on load,100~240VAC 50/ 60Hz
Grounding Terminal	1xGrounding Terminal
Operating Temperature	-10°C~45°C
Storage Temperature	-40°C~+85°C
Humidity	0~95%
Single Port Power Output	Single Port PoE Power Output≤30W, Voltage 54VDC
Dimensions	442mm x 285mm x 44.5mm
Color	Black
Power Light	1x Red LED