

CP-UVR-1601E1V3**16 Ch. Tribrid 720P Compact 1U HDCVI DVR****Main Features**

- Support HDCVI/Analog/IP Video input
- All channel 1080N/720P recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 6TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



CP-UVR-1601E1V3

16 Ch. Tribrid 720P Compact 1U HDCVI DVR

Feature

Processor
Operating System
Two-way Talk
User Interface
Video Input
Video Output
Video Standard
Compression
Video Resolution
Video Recording
Video Display Split
Privacy Masking
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Hard Disk
Smart Phone
Trigger Events
Recording Mode
Search Mode

Playback

Backup Mode
Max User Account
Record Interval
Interface Ports
Ethernet

Specification

Embedded processor
Embedded LINUX
Reuse audio input/output channel 1
GUI
16 channel, BNC
1 HDMI, 1 VGA
Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s), HDCVI: 720P HDCVI Camera, IP: 1080P/720P/D1/CIF IP Camera
H.264 / G.711
1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768
Main Stream: 1*1080N/720P(1~25/30fps)+15*(1~12/15fps) /960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps, Extra Stream: CIF/QCIF(1~25/30fps)
1/4/8/9/16
4 rectangular zones (each camera)
1 channel, RCA
1 channel, RCA
Supports
Supports
Supports
1 SATA port, up to 6TB
iPhone, iPad, Android, Windows Phone
Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
Manual, Schedule(Regular(Continuous), MD), Stop
Time/Date, MD & Exact search (accurate to second)

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

USB Device/Internal SATA burner/Network
128 users
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
1 HDMI, 1 VGA, 2 USB2.0, 1 RS485
RJ-45 port (10/100M)

CP-UVR-1601E1V3**16 Ch. Tribrid 720P Compact 1U HDCVI DVR****Feature**

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P, ONVIF Version 2.4 conformance

DC12V/2A

10W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

260mm × 220mm × 40mm

0.75KG(without HDD)