

# CP- UVR-1601E2-S

16 Ch. 1080P Lite Cosmic HD DVR

**COSMIC**  
HD DVR



## Main Features

- Auto Adaptive HDCVI/AHD/TVI/CVBS signals
- Support upto 5MP IP Camera
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Max 72Mbps Incoming Bandwidth
- Support 2 SATA HDD up to 12TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB
- CMS Software:KVMS, KVMS Pro



\*Product casing and specifications are subject to change without prior notice

# CP- UVR-1601E2-S

## 16 Ch. 1080P Lite Cosmic HD DVR

**COSMIC**  
HD DVR

### Feature

Processor  
Operating System  
IP Camera Input  
Two-way Talk  
User Interface  
HD Camera Input  
Video Output  
Video Standard  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
Audio Input  
Audio Output  
Motion Detection  
Video Loss  
Camera Blank  
Smart Phone  
Hard Disk  
Trigger Events  
Recording Mode  
Search Mode  
Playback  
Backup Mode  
Interface Ports  
Record Interval  
Max User Account  
Ethernet

### Specification

Embedded processor  
Embedded LINUX  
16+2 Channel, each channel up to 5MP  
1 Channel Input, 1 Channel Output, RCA  
GUI  
16 channel  
1 HDMI, 1 VGA  
Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)  
H.264  
1080N(960 x 1080), 720P, 960H, D1, HD1, BCIF, CIF, QCIF  
Main Stream: 1Ch. @1080N/720P(1~25/30fps)+15Ch. @(1~12/15fps)/ 960H/D1/HD1 /BCIF/  
CIF/QCIF (1~25/30fps), Sub steram: D1/CIF/QCIF(1~25/30fps)  
1/4/8/9/16/25  
1 channel, RCA  
1 channel, RCA  
MD Zones: 396 (22 x 18)  
Supports  
Supports  
iPhone, iPad, Android Phone  
2 SATA port, up to 12TB  
Recording, PTZ, Tour, Alram Out, Video Push, Email, FTP, Spot, Buzzer & Screen tips  
Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video  
Loss, Tampering), Alarm, Stop  
Time/Date,Alram, MD & Exact search (accurate to second)  
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file,Next camera, Previous  
camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom  
USB Device/Network  
1 HDMI, 1 VGA, 2 USB (1 USB 2.0 , 1 USB 3.0), 1 RS485  
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
128 users  
RJ-45 port (10/100M)



\*Product casing and specifications are subject to change without prior notice

# CP-UVR-1601E2-S

16 Ch. 1080P Lite Cosmic HD DVR

**COSMIC**  
HD DVR

## Feature

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

## Specification

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 2.4.1, CGI Conformant

DC12V/4A

<15W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm × 285mm × 55mm

1.8 KG(without HDD)