

CP- UVR-1601K2-S

16 Ch. 1080P Cosmic HD DVR





Main Features

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 5MP IP Camera
- All channel 1080P Non-Realtime Recording
- H.264 Plus /H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 2 SATA HDD up to 16TB, 2 USB Ports
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



















CP- UVR-1601K2-S

16 Ch. 1080P Cosmic HD DVR



Feature Specification

Processor Embedded processor

IP Camera Input 16+8: each channel up to 5MP

Operating System Embedded LINUX
Two-way Talk Reuse audio in/out, RCA

User Interface GUI

Video Input 16 channel, BNC

Video Output 1 HDMI ,1 VGA SPOT(configurable)

Video Standard Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)

Compression H.264+/H.264

Video Resolution $1920 \times 1080, 1280 \times 1024, 1280 \times 720, 1024 \times 768$

Video Recording

Main stream: 1080P(1~15fps) 1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps), Sub

stream: D1/CIF/QCIF($1\sim25/30fps$)

Video Display Split 1/4/8/9/16/25
Audio Input 1 channel
Audio Output 1 channel
Motion Detection Supports
Video Loss Supports
Camera Blank Supports

Smart Phone iPhone, iPad, Android, Phone
Hard Disk 2 SATA port, up to 16TB

Trigger Events Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips

Recording Mode Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video

Loss, Tampering), Alarm, Stop

Search Mode Time / Date, Alarm, MD and Exact Search (accurate to second)

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous

camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

Backup Mode USB Device/Network

Interface Ports 1 HDMI, 1 VGA, 2 USB Ports, 1 RS485, 1 RJ45

Max User Account 128 users

Record Interval 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

Ethernet RJ-45 port (1000M)







16 Ch. 1080P Cosmic HD DVR



Feature

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 2.4.1, CGI Conformant

DC12V/4A

<15W (Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm x 287mm x 53mm

2.35KG (without HDD)



