

CP- UVR-1601L1-4K

16 Ch. 4K Cosmic DVR



Main Features

- Support HDCVI/AHD/TVI/CVBS/IP video inputs
- Support upto 8MP IP Camera
- H.264+ / H.264 dual-stream video compression
- Max 96Mbps Incoming Bandwidth
- All channel 4K Non-Realtime Recording
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 8TB, 2 USB Ports
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



*Product casing and specifications are subject to change without prior notice

CP- UVR-1601L1-4K

16 Ch. 4K Cosmic DVR



Feature

Processor
 IP Camera Input
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Smart Phone
 Hard Disk
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Interface Ports
 Max User Account
 Record Interval

Specification

Embedded processor
 16+8 Channel, each channel up to 8MP
 Embedded LINUX
 Reuse audio in/out, RCA
 GUI
 16 channel, BNC
 1 HDMI, 1 VGA
 NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
 H.264+/H.264
 4K, 5MP, 4MP, 3MP, 1080P, 720P, 960H, D1, CIF, QCIF
 Main stream: 4K(1~7fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 1080P/720P/960H/D1/CIF/QCIF (1~25/30fps) , Sub stream: 960H(1~15fps); D1/CIF/QCIF(1~25/30fps)
 1/4/8/9/16/25
 1 channel, RCA
 1 channel, RCA
 MD Zones: 396 (22 × 18)
 Supports
 Supports
 iPhone, iPad, Android Phone
 1 SATA port, up to 8TB
 Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
 Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
 Time /Date, Alarm, MD and Exact Search (accurate to second)
 Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom
 USB Device / Network
 1 HDMI, 1 VGA, 1 RS485, 2 USB Ports(1 USB 2.0 , 1 USB 3.0)
 128 users
 1 ~ 60 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec



*Product casing and specifications are subject to change without prior notice

CP- UVR-1601L1-4K

16 Ch. 4K Cosmic DVR



Feature

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

1 RJ-45 Port (1000M)

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 2.42, CGI Conformant

DC12V/3A

<15W (Without HDD)

-10 ~+55°C / 10~90%RH

325mm x 255mm x 55mm

1.5KG(without HDD)