

## CP- UVR-1604E2-S

16 Ch. 1080P Lite Cosmic HD DVR





### **Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 5MP IP Camera
- All channel 1080P Lite Non-Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 2 SATA HDD up to 12TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



















# CP- UVR-1604E2-S

## 16 Ch. 1080P Lite Cosmic HD DVR



Feature Specification

Processor Embedded processor

IP Camera Input 16+2 Channel, each channel up to 5MP

Operating System Embedded LINUX

Two-way Talk Reuse audio in (channel 1)/out, RCA

User Interface GUI

HD Camera Input 16 channel
Video Output 1 HDMI, 1 VGA

Video Standard Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)

Compression H.264

Video Resolution 1920×1080, 1280×1024, 1280×720, 1024×768

Video Recording

Main Stream: 1080N(12fps)/720P(15fps)/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps), Sub

stream: D1/CIF/QCIF(1~25/30fps)

Video Display Split 1/4/8/9/16/25
Audio Input 4 channel
Audio Output 1 channel

Motion Detection MD Zones: 396 (22  $\times$  18)

Video Loss Supports
Camera Blank Supports

Recording Mode

Smart Phone iPhone, iPad, Android Phone
Hard Disk 2 SATA port, up to 12TB

Trigger Events Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips

Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video

Loss, Tampering), Alarm, Stop

Search Mode Time/Date, Alarm, MD & Exact search (accurate to second)

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous

camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

Backup Mode USB Device/Network

Record Interval 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

Interface Ports 1 HDMI, 1 VGA, 2 USB, 1 RS485, 1 RJ45

Max User Account 128 users

Ethernet RJ-45 port (100M)





## CP- UVR-1604E2-S

16 Ch. 1080P Lite Cosmic HD DVR



### **Feature**

Protocols

**Power Supply** 

**Power Consumption** 

Working Temp

Dimensions

Weight

### **Specification**

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P,IP Search, ONVIF 2.4.1, CGI Conformant

DC12V/4A

<15W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm  $\times 285$ mm  $\times 55$ mm

2.35KG (without HDD)



