

CP- UVR-1604K2-S

16 Ch. 1080P Cosmic HD DVR





Main Features

- Auto Adaptive HDCVI/AHD/TVI/CVBS signals
- Support upto 5MP IP Camera
- All channel 1080P Lite Realtime or 1080P non-Realtime Recording
- H.264Plus/ H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 2 SATA HDD up to 12TB, 2 USB(1 USB 2.0, 1 USB 3.0)
- Mobile Software: iCMOB, gCMOB
- CMS Software:KVMS, KVMS Pro



















CP- UVR-1604K2-S

16 Ch. 1080P Cosmic HD DVR



Feature

Processor Embedded processor

IP Camera Input 16+8 Channel, each channel up to 5MP

Operating System Embedded LINUX

Two-way Talk Reuse audio input/output channel 1

User Interface GUI

Video Input 16 channel, BNC
Video Output 1 HDMI, 1 VGA

Video Standard Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)

Specification

Compression H.264+/H.264

Video Resolution $1920 \times 1080, 1280 \times 1024, 1280 \times 720, 1024 \times 768$

Video Recording

Main Stream: 1080P(1~12/15fps) / 1080N/720P/960H / D1(1~25/30fps), Extra Stream: D1/

CIF / QCIF(1~25/30fps)

Video Display Split 1/4/8/9/16/25
Audio Input 4 channel, RCA
Audio Output 1 channel, RCA
Motion Detection Supports
Video Loss Supports
Camera Blank Supports

Alarm Input 16 channel
Alarm Output 3 channel

Smart Phone iPhone, iPad, Android Phone
Hard Disk 2 SATA port, up to 12TB

Trigger Events Recording, PTZ, Alram Out, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips

Recording Mode Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video

Loss, Tampering), Alarm, Stop

Search Mode Time/Date, Alram, MD & Exact search (accurate to second)

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous

camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

Backup Mode USB Device/Network

Max User Account 128 users

Record Interval 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec







16 Ch. 1080P Cosmic HD DVR



Feature

Interface Ports

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

1 HDMI, 1 VGA, 2 USB(1 USB 2.0, 1 USB 3.0)

RJ-45 port (10/100M/1000M)

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS,

FTP, Alarm Server, IP Search, ONVIF 2.4.1, CGI Conformant

DC12V/4A

<15W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm × 285mm × 55mm

2.35KG(without HDD)



