

CP- UVR-1616F1-S

16Ch. 1080P Cosmic HD DVR

COSMIC
HD DVR



Main Features

- Auto Adaptive HDCVI/AHD/TVI/CVBS signals
- Support upto 5MP IP Camera
- All channel 1080P Realtime Recording
- H.264Plus/ H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 6TB, 1 USB 2.0 , 1 USB 3.0
- Mobile Software: iCMOB, gCMOB
- CMS Software:KVMS, KVMS Pro



CP-UVR-1616F1-S

16Ch. 1080P Cosmic HD DVR

COSMIC
HD DVR

Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Input
Video Output
Video Standard
Compression
Video Resolution
Video Recording
Video Display Split
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Smart Phone
Hard Disk
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Record Interval
Interface Ports

Specification

Embedded processor
16+8 Channel, each channel up to 5MP
Embedded LINUX
Reuse audio in(channel 1)/out, RCA
GUI
16 channel, BNC
1 HDMI, 1 VGA
Analog: NTSC/PAL
H.264+/H.264
1920×1080, 1280×1024, 1280×720, 1024×768
Main Stream: 1080P/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps), Extra Stream: D1/CIF/QCIF(1~25/30fps)
1/4/8/9/16/25
16 channel, RCA
1 channel, RCA
Supports
Supports
Supports
16 channel
3 Channel
iPhone, iPad, Android Phone
1 SATA port, up to 6TB
Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Spot, Buzzer & Screen tips
Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Time/Date, Alarm, MD & Exact search (accurate to second)
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom
USB Device/Network
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
1 HDMI, 1 VGA, 1 USB 2.0, 1 USB 3.0, 1 RS485



*Product casing and specifications are subject to change without prior notice

CP-UVR-1616F1-S

16Ch. 1080P Cosmic HD DVR

COSMIC
HD DVR

Feature

Max User Account

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

128 users

RJ-45 port (10/100M/1000M)

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 2.4.1, CGI Conformant

DC12V/3A

<15W(without HDD)

-10 ~ +55°C / 10~90%RH / 86~106kpa

325mm × 255mm × 55mm

1.5Kg(without HDD)