

CP- ER-3216E2-T**32 Ch. 1080P Lite Astra DVR****Astra** HD
DVR**Main Features**

- H.264 dual-stream video compression
- All channel 1080P Lite Non-Realtime Recording
- Support AHD, TVI, CVI, CVBS, IP Video input
- HDMI / VGA simultaneous video output
- Support 2 SATA Ports up to 16TB, 3 USB2.0
- Mobile Software: RMOB
- CMS Software: RVMS



*Product casing and specifications are subject to change without prior notice

CP- ER-3216E2-T

32 Ch. 1080P Lite Astra DVR



Feature

Processor
Operating System
User Interface
Video Input
Video Output
Video Standard
Compression
Video Resolution
Video Recording
Video Display Split
Audio Input
Audio Output
Alarm Input
Alarm Output
Hard Disk
Smart Phone
HDD Management
Recording Mode
Search Mode
Playback
Backup Mode
Interface Ports
Ethernet
Protocols
Power Supply
Power Consumption
Working Temp
Dimensions
Weight

Specification

High performance embedded microprocessor
Embedded LINUX
GUI
32 channel, BNC
1 HDMI, 1 VGA
Analog: 32Ch. @1080N, 16Ch. @1080N, 32Ch. @960H / Hybrid: 16Ch. @1080N(analog)+ 16Ch. @960P(ip) / IP: 16Ch. @1080P+16Ch. @960P, 8Ch. @3M, 8Ch. @5M
H.264 / G.711a
1920x1080, 1280x1024, 1280x720, 1024x768, 800x600
32Ch. @1080N@12fps, 16Ch. @960H, 16Ch. @1080N
1/4/8/9/16/25/32
16 channel
1 channel
16 Channel
4 Channel
2 SATA port, up to 16TB
iPhone, iPad, Android
HDD Storage, Network Storage
Manual> Alarm> Motion detection> Timing
Search by Time/Calendar/Event/Channel
16Ch.
Network, USB, SATA
3 USB 2.0, 1 RS485, 1 RS232, 1 RJ45
RJ45 10M/100M Adaptive Ethernet port
HTTP, TCP/IP, UDP, IPV4, UPNP, RTSP, SMTP, NTP, DHCP, DNS, FTP, P2P, ONVIF, CGI
12V/4A
<10W(Without HDD)
0 °C - + 55 °C, 10% -90% RH
440mm(L) x 290mm(W) x 50mm(H)
3KG