

CP- UVR-3201E2-S

32 Ch. 1080P Lite Cosmic HD DVR



Main Features

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 5MP IP Camera
- All channel 1080P Lite Non-Realtime Recording
- H.264 dual-stream Video Compression
- Support 2 SATA Ports up to 16TB, 2 USB (1 USB 3.0,1 USB 2.0)
- HDMI / VGA Simultaneous Video Output
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



CP- UVR-3201E2-S

32 Ch. 1080P Lite Cosmic HD DVR



Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
HD Camera Input
Video Output
Video Standard
Compression
Video Resolution
Video Recording
Video Display Split
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Smart Phone
Hard Disk
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Interface Ports
Max User Account
Record Interval
Ethernet

Specification

Embedded processor
16 Channel, each channel up to 5MP
Embedded LINUX
Reuse audio in/out, RCA
GUI
32 Channel
1 HDMI, 1 VGA, 1 TV
Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
H.264
1080N(960 x 1080), 720P, 960H, D1, HD1, BCIF, CIF, QCIF
Main Stream: 1080N(12fps)/720P(15fps)/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps), Sub stream: CIF/QCIF(1~7fps)
1/4/8/9/16/25
1 channel, RCA
1 channel, RCA
MD Zones: 396 (22 x 18)
Supports
Supports
iPhone, iPad, Android Phone
2 SATA port, up to 16TB
Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Time /Date, Alarm, MD and Exact Search (accurate to second)
Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom
USB Device/Network
1 HDMI, 1 VGA, 1 TV, 2 USB (1 USB 2.0, 1 USB 3.0), 1 RS485
128 users
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
RJ-45 port (1000M)



CP- UVR-3201E2-S

32 Ch. 1080P Lite Cosmic HD DVR



Feature

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 2.4.1, CGI Conformant

DC12V/4A

<20W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm x 287mm x 53mm

2 KG (without HDD)