

CP- UVR-3201E2-V3**32Ch. Tribrid 720P HDCVI DVR****Main Features**

- Support HDCVI/Analog/IP Video input
- All channel 1080N/720P Realtime Recording
- H.264 dual-stream Video Compression
- Advanced intelligent functions: Tripwire, Intrusion, Abandoned/Missing, Face Detection, P2P
- HDMI / VGA Simultaneous Video Output
- Support 2 SATA HDD up to 12TB, 2 USB2.0
- ONVIF Version 2.4.1 conformance
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



**Product casing and specifications are subject to change without prior notice*

CP- UVR-3201E2-V3

32Ch. Tribrid 720P HDCVI DVR



Feature

Processor
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Privacy Masking
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Smart Phone
 Hard Disk
 Trigger Events
 Recording Mode
 Search Mode

Specification

Embedded processor
 Embedded LINUX
 Reuse audio input/output channel 1
 GUI
 32 channel, BNC
 1 HDMI, 1 VGA, TV,SPOT (configurable)
 Analog: NTSC/ PAL, HDCVI: 1080P/720P HDCVI Camera, IP: 16 channel up to 5Mp
 H.264 / G.711
 1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768
 Main Stream: 1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF(1~25/30fps), Extra Stream:CIF/QCIF (1~15fps)
 1/4/8/9/16/25/36
 4 rectangular zones (each camera)
 1 channel, RCA
 1 channel, RCA
 Supports
 Supports
 Supports
 iPhone, iPad, Android, Windows Phone
 2 SATA port, up to 12TB
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
 Manual, Schedule(Regular(Continuous), MD), Stop
 Time/Date, MD & Exact search (accurate to second)

Playback

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

Backup Mode

USB Device/Internal SATA burner/Network

Record Interval

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

Max User Account

128 users

Interface Ports

1 HDMI, 1 VGA, 2 USB2.0, 1 RS485

Ethernet

RJ-45 port (10/100M)

Protocols

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P



CP- UVR-3201E2-V3

32Ch. Tribrid 720P HDCVI DVR



Feature

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

DC12V/5A

20W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm × 285mm × 55 mm

2.35KG(without HDD)