

CP- UVR-3204K4D-S**32 Ch. 1080P Cosmic HD DVR****Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS signals
- Support upto 5MP IP Camera
- H.264+/ H.264 dual-stream Video Compression
- All channel 1080P Recording
- 2 HDMI / 1 VGA / 1 TV Simultaneous Video Output
- Support Multi-brand network cameras
- Support 4 SATA HDDs up to 8TB capacity for each disk, 1 eSATA, 3 USB(1USB2.0, 2USB3.0)
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



**Product casing and specifications are subject to change without prior notice*

CP- UVR-3204K4D-S

32 Ch. 1080P Cosmic HD DVR



Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Input
Video Output
Video Standard
Compression
Video Resolution
Video Recording
Video Display Split
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Smart Phone
Hard Disk
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Interface Ports
Max User Account

Specification

Embedded processor
32 Channel, each channel up to 5MP
Embedded LINUX
1 channel Input, 1 channel Output, BNC
GUI
32 channel, BNC
2 HDMI, 1 VGA, 1 TV
Analog: NTSC/PAL
H.264+/H.264
1920×1080, 1280×1024, 1280×720, 1024×768
Main Stream: 1080P(1~15fps) 1080N/720P/960H/D1/HD1/2CIF/CIF(1~25/30fps), Extra Stream: D1/ CIF/QCIF(1~25/30fps)
1/4/8/9/16/25/36
4 channel, RCA
1 channel, RCA
Supports
Supports
Supports
16 Channel
6 Channel
iPhone, iPad, Android Phone
4 SATA port up to 8TB Capacity for each disk, 1 eSATA port
Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Spot, Buzzer & Screen tips
Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Time /Date, Alarm, MD and Exact Search (accurate to second), Smart search
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom
USB Device/Network
2 HDMI, 1 VGA, 1 TV, 1 RS485, 1 RS232, 3 USB(1 USB 2.0 , 2 USB 3.0)
128 users



CP- UVR-3204K4D-S

32 Ch. 1080P Cosmic HD DVR



Feature

Record Interval

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

RJ-45 port (10/100M/1000M)

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 2.4.1, CGI Conformant

AC 100~240 V, 50/60 Hz

<30W(Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm×417mm×76mm

6KG (without HDD)