

CP- ER-0404D2-5M**4 Ch. 5MP Astra DVR****Astra** HD
DVR**Main Features**

- H.264+ /H.264 dual-stream video compression
- All channel 5MP Non-Realtime Recording
- Support AHD, TVI,CVI, CVBS, IP Video input
- HDMI / VGA simultaneous video output
- Support 2 SATA Port up to 16TB, 2 USB Ports(2.0)
- Mobile Software: cMOB-20
- CMS Software: RVMS Pro



**Product casing and specifications are subject to change without prior notice*

CP- ER-0404D2-5M

4 Ch. 5MP Astra DVR

Astra HD
DVR

Feature

Processor
Operating System
User Interface
Video Input
Video Output

Video Standard

Compression
Video Resolution
Live Preview

Video Recording

Video Display Split
Audio Input
Audio Output
Alarm Input
Alarm Output
Hard Disk
Smart Phone
HDD Management
Recording Mode
Search Mode
Playback
Backup Mode
Interface Ports
Wi-Fi
Ethernet
Protocols
Power Supply
Power Consumption

Specification

High performance embedded microprocessor
Embedded LINUX
GUI
4 channel, BNC
1 HDMI, 1 VGA

Analog: 4Ch. 5MP@11fps(AHD) , 4Ch. 4MP@15fps(AHD) , 4Ch. 3MP@18fps(AHD) , 4Ch. 1080P@25fps(5 in 1) / Hybrid: 2Ch. @5MP(analog) + 2Ch. @5MP(ip) / IP: 8Ch. @1080P+ 8Ch. @960P, 4Ch. @5MP, 4Ch. @3MP

H.264+ / H.264 / G.711a
5MP, 4MP, 3MP, 2MP, 1MP
4Ch. 5MP@20fps , 4Ch. @4MP

4Ch. 5MP@11fps(AHD) , 4Ch. 4MP@15fps(AHD) , 4Ch. 3MP@18fps(AHD) , 4Ch. 1080P@25fps (5 in 1)

1/4
4 channel
1 channel
4 channel
1 channel
2 SATA port, up to 16TB
iPhone, iPad, Android
HDD Storage, Network Storage
Manual> Alarm> Motion detection> Timing
Search by Time/Calendar/Event/Channel
4Ch.
Network, USB, SATA
2 USB Ports(2.0), 1 RS485, 1 RJ45
Support 3G
RJ45 10/100Mbps Adaptive Ethernet port
HTTP, TCP/IP, UDP, IPV4, UPNP, RTSP, SMTP, NTP, DHCP, DNS, FTP, P2P, ONVIF, CGI
12V/4A
<10W(Without HDD)



**Product casing and specifications are subject to change without prior notice*

CP- ER-0404D2-5M

4 Ch. 5MP Astra DVR

Astra HD
DVR

Feature

Working Temp

Dimensions

Weight

Specification

0 °C - + 55 °C, 10% -90% RH

310mm(L) x 298mm(W) x 60mm(H)

1.8 KG