

CP- UVR-0401D1-4M

4 Ch. 4MP Cosmic DVR



Main Features

- Support HDCVI/AHD/TVI/CVBS/IP video inputs
- Support upto 5MP IP Camera
- H.264+ / H.264 dual-stream video compression
- Max 24Mbps Incoming Bandwidth
- All channel 4MP Non-Realtime Recording
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 8TB, 2 USB Ports
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



*Product casing and specifications are subject to change without prior notice

CP- UVR-0401D1-4M

4 Ch. 4MP Cosmic DVR



Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Input
Video Output
Video Standard
Compression
Video Resolution
Video Recording
Video Display Split
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Smart Phone
Hard Disk
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Interface Ports
Max User Account
Record Interval
Ethernet

Specification

Embedded processor
4+2 Channel, each channel up to 5MP
Embedded LINUX
Reuse audio in/out, RCA
GUI
4 channel, BNC
1 HDMI, 1 VGA
NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
H.264+/H.264
4MP, 3MP, 1080P, 720P, 960H, D1, CIF, QCIF
Main stream: 4MP/3MP(1~15fps); 1080P/720P/960H/D1/CIF/QCIF (1~25/30fps), Sub Stream: 960H(1~12fps); D1/CIF/QCIF(1~25/30fps)
1/4/6
1 channel, RCA
1 channel, RCA
MD Zones: 396 (22 × 18)
Supports
Supports
iPhone, iPad, Android Phone
1 SATA port, up to 8TB
Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Time /Date, Alarm, MD and Exact Search (accurate to second)
Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom
USB Device / Network
1 HDMI, 1 VGA, 1 RS485, 2 USB Ports (2 USB 2.0)
128 users
1 ~ 60 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec
1 RJ-45 Port (100M)



CP- UVR-0401D1-4M

4 Ch. 4MP Cosmic DVR



Feature

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 2.42, CGI Conformant

DC12V/2A

<10W (Without HDD)

-10 ~+55°C / 10~90%RH

325mm x 255mm x 55mm

1.5KG(without HDD)