

CP- UVR-0404E4D

4 Ch. 720P Tribrid HDCVI DVR

CP PLUS
CORAL



Main Features

- Tribrid: Each channel supports Analog/HDCVI/IP Video input
- All channel 720P Recording
- H.264 dual-stream Video Compression
- HDMI / VGA / TV Simultaneous Video Output
- Support Multi-brand network cameras:
- Support 4 SATA HDDs up to 16TB, 1 eSATA, 3 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



*Product casing and specifications are subject to change without prior notice

CP- UVR-0404E4D

4 Ch. 720P Tribrid HDCVI DVR



Feature

Processor
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Privacy Masking
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Alarm Input
 Alarm Output
 Smart Phone
 Hard Disk
 Trigger Events
 Recording Mode
 Search Mode

 Playback

 Backup Mode
 Interface Ports
 Max User Account
 Record Interval

Specification

Embedded processor
 Embedded LINUX
 1 channel Input,1 channel Output, BNC
 GUI
 4 channel, BNC
 1 HDMI, 1 VGA ,1 TV
 Analog: NTSC/PAL, HDCVI: 720P HDCVI Camera, IP: 2ch: 1080P/720P IP Camera
 H.264 / G.711
 1920×1080, 1280×1024, 1280×720, 1024×768
 Main Stream: 1*720P(1~25/30fps)+3*720P(1~15fps)/4*960H(1~25/30fps), Extra Stream: CIF/ QCIF(1~25/30fps)
 1/4
 4 rectangular zones (each camera)
 4 channel, RCA
 1 channel, RCA
 Supports
 Supports
 Supports
 8 Channel
 6 Channel
 iPhone, iPad, Android, Windows Phone
 4 SATA ports(4 HDDs or 3HDDs+1 CD/DVD-RW), up to 16TB, 1 eSATA port
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
 Manual, Schedule(Regular(Continuous), MD), Stop
 Time/Date, MD & Exact search (accurate to second)

 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file,Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

 USB Device/eSATA Device/Internal SATA burner/Network
 1 RS485, 1 RS 422, 1 RS232, 3 USB2.0
 128 users
 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec



*Product casing and specifications are subject to change without prior notice

CP- UVR-0404E4D

4 Ch. 720P Tribrid HDCVI DVR



Feature

Ethernet
Protocols
Power Supply
Power Consumption
Working Temp
Dimensions
Weight

Specification

RJ-45 port (10/100M/1000M)
HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP
AC 100~240 V, 50/60 Hz
40W(Without HDD)
-10 ~+55°C / 10~90%RH / 86~106kpa
440mm× 416mm× 68mm
6 KG(without HDD)