

CP- ER-0808D2-5M**8 Ch. 5MP Astra DVR****Astra** HD
DVR**Main Features**

- H.264+ /H.264 dual-stream video compression
- All channel 5MP Non-Realtime Recording
- Support AHD, TVI,CVI, CVBS, IP Video input
- HDMI / VGA simultaneous video output
- Support 2 SATA Port up to 16TB, 2 USB Ports(2.0)
- Mobile Software: cMOB-20
- CMS Software: RVMS Pro



**Product casing and specifications are subject to change without prior notice*

CP- ER-0808D2-5M

8 Ch. 5MP Astra DVR



Feature

Processor
 Operating System
 User Interface
 Video Input
 Video Output

 Video Standard

 Compression
 Video Resolution
 Live Preview

 Video Recording

 Video Display Split
 Audio Input
 Audio Output
 Alarm Input
 Alarm Output
 Hard Disk
 Smart Phone
 HDD Management
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Interface Ports
 Wi-Fi
 Ethernet
 Protocols
 Power Supply
 Power Consumption
 Working Temp

Specification

High performance embedded microprocessor
 Embedded LINUX
 GUI
 8 channel, BNC
 1 HDMI, 1 VGA

 Analog: 8Ch. 5MP@11fps(AHD) , 8Ch. 4MP@15fps(AHD) , 8Ch. 3MP@18fps(AHD) , 8Ch. @1080P(5 in 1) / Hybrid: 4Ch. @5MP(analog) + 4Ch. @5MP(ip) / IP: 8Ch. @3MP , 4Ch. @5MP

 H.264+ / H.264 / G.711a
 5MP, 4MP, 3MP, 2MP, 1MP
 8Ch. 5MP@20fps(AHD) , 8Ch. @4MP

 8Ch. 5MP@11fps(AHD) , 8Ch. 4MP@15fps(AHD) , 8Ch. 3MP@18fps(AHD) , 8Ch. @1080P(5 in 1)

 1/4/8/9
 8 channel
 1 channel
 4 channel
 1 channel
 2 SATA port, up to 16TB
 iPhone, iPad, Android
 HDD Storage, Network Storage
 Manual> Alarm> Motion detection> Timing
 Search by Time/Calendar/Event/Channel
 8Ch.
 Network, USB, SATA
 2 USB Ports(2.0), 1 RS485, 1 RJ45
 Support 3G
 RJ45 10/100Mbps Adaptive Ethernet port
 HTTP, TCP/IP, UDP, IPV4, UPNP, RTSP, SMTP, NTP, DHCP, DNS, FTP, P2P, ONVIF, CGI
 12V/4A
 <10W(Without HDD)
 0 °C - + 55 °C, 10% -90% RH



*Product casing and specifications are subject to change without prior notice

CP- ER-0808D2-5M

8 Ch. 5MP Astra DVR

Astra HD
DVR

Feature

Dimensions

Weight

Specification

310mm(L) x 298mm(W) x 60mm(H)

1.8 KG