

CP- UVR-0801C1
8 Ch. 720P HDCVI DVR

CP PLUS
CORAL



Main Features

- All channel 720P Recording
- Support HDCVI/Analog Video input
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 4TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



CP- UVR-0801C1

8 Ch. 720P HDCVI DVR



Feature

Processor
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Privacy Masking
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Smart Phone
 Hard Disk
 Trigger Events
 Recording Mode
 Search Mode

Specification

Embedded processor
 Embedded LINUX
 Reuse audio input/output channel 1
 GUI
 8 channel, BNC
 1 HDMI, 1 VGA
 Analog: NTSC/PAL, HDCVI: 720P HDCVI Camera
 H.264 / G.711
 1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768, 800 × 600
 Main Stream: 720P(1~12fps)/960H(1~20fps)/D1/(1~25/30fps), CIF/QCIF(1~25/30fps), D1
 1/4/8/9
 4 rectangular zones (each camera)
 1 channel, RCA
 1 channel, RCA
 Supports
 Supports
 Supports
 iPhone, iPad, Android, Windows Phone
 1 SATA port, up to 4TB
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
 Manual, Schedule(Regular(Continuous), MD), Stop
 Time/Date, MD & Exact search (accurate to second)

Playback

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

Backup Mode

USB Device/Internal SATA burner/Network

Record Interval

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

Max User Account

128 users

Interface Ports

1 HDMI, 1 VGA, 1 RS485, 2 USB2.0

Ethernet

RJ-45 port (10/100M)

Protocols

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP

Power Supply

DC12V/2A



**CP- UVR-0801C1**
8 Ch. 720P HDCVI DVR**Feature**

Power Consumption

Working Temp

Dimensions

Weight

Specification

10W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

260mm × 220mm × 40mm

0.75Kg(without HDD)