

# CP- UVR-0801E2-S

8 Ch. 1080P Lite Cosmic DVR

**COSMIC**  
HD DVR



## Main Features

- Auto Adaptive HDCVI / CVBS / HDTV / AHD video inputs
- Support upto 5MP IP Camera
- H.264 Video Compression
- Max 40 Mbps Incoming Bandwidth
- HDMI / VGA Simultaneous Video Output
- Support 2 SATA HDD up to 12TB, 2 USB(1 USB 2.0 , 1 USB 3.0)
- Mobile Software: iCMOB, gCMOB
- CMS Software:KVMS, KVMS Pro



*\*Product casing and specifications are subject to change without prior notice*

# CP- UVR-0801E2-S

## 8 Ch. 1080P Lite Cosmic DVR

**COSMIC**  
HD DVR

### Feature

Processor  
IP Camera Input  
Operating System  
Two-way Talk  
User Interface  
HD Camera Input  
Video Standard  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
Audio Input  
Audio Output  
Motion Detection  
Video Loss  
Camera Blank  
Hard Disk  
Smart Phone  
Trigger Events  
Recording Mode  
Search Mode  
Playback  
Backup Mode  
Max User Account  
Interface Ports  
Record Interval  
Ethernet  
Protocols

### Specification

Embedded processor  
8+2 Channel, each channel up to 5MP  
Embedded LINUX  
1 Channel Input, 1 Channel Output, RCA  
GUI  
8 Channel  
NTSC/PAL  
H.264  
1080N(960 x 1080), 720P, 960H, D1, HD1, BCIF, CIF, QCIF  
Main Stream: 1Ch. @1080N/720P(1~25/30fps) +7Ch. @(1~12/15fps)/960H/D1/HD1/ BCIF/ CIF/QCIF (1~25/30fps), Sub Stream: BCIF/CIF/QCIF (1~25/30fps)  
1/4/8/9/16  
1 Channel  
1 Channel  
MD Zones: 396 (22 x 18)  
Supports  
Supports  
2 SATA port, up to 12TB  
iPhone, iPad, Android  
Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips  
Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop  
Time /Date, Alarm, MD and Exact Search (accurate to second)  
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom  
USB Device/Network  
128 users  
1 HDMI, 1 VGA, 2 USB(1 USB 2.0 , 1 USB 3.0), 1 RS485  
1 ~ 120 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec  
RJ-45 port (100M)  
HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search, ONVIF 2.4.1, CGI Conformant



\*Product casing and specifications are subject to change without prior notice

**CP-UVR-0801E2-S**  
8 Ch. 1080P Lite Cosmic DVR

**COSMIC**  
HD DVR

**Feature**

Power Supply  
Power Consumption  
Working Temp  
Dimensions  
Weight

**Specification**

DC12V/4A  
<15W(without HDD)  
-10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa / 0 ~ 90% RH  
375mm × 285mm × 55mm  
1.8 Kg.(without HDD)