

**CP- UVR-0801FM1****8 Ch. 4MP HDCVI DVR****Main Features**

- Support HDCVI / CVBS video inputs
- Support upto 5MP IP Camera
- H.264+ / H.264 dual-stream video compression
- Max 48Mbps Incoming Bandwidth
- All channel 4MP Non-Realtime Recording
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 6TB, 2 USB Ports
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



# CP- UVR-0801FM1

## 8 Ch. 4MP HDCVI DVR



### Feature

Processor  
 IP Camera Input  
 Operating System  
 Two-way Talk  
 User Interface  
 Video Input  
 Video Output  
 Video Standard  
 Compression  
 Video Resolution  
 Video Recording  
 Video Display Split  
 Audio Input  
 Audio Output  
 Motion Detection  
 Video Loss  
 Camera Blank  
 Smart Phone  
 Hard Disk  
 Trigger Events  
 Recording Mode  
 Search Mode  
 Playback  
 Backup Mode  
 Interface Ports  
 Max User Account  
 Record Interval  
 Ethernet

### Specification

Embedded processor  
 8+4 Channel, each channel up to 5MP  
 Embedded LINUX  
 Reuse audio in/out, RCA  
 GUI  
 8 channel, BNC  
 1 HDMI (up to 3840 x 2160), 1 VGA  
 NTSC(525Line, 60f/s), PAL(625Line, 50f/s)  
 H.264+/H.264  
 4MP, 1080P, 720P, 960H, D1, HD1, BCIF, CIF, QCIF  
 Main stream: 4MP(1-15fps) 1080P/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps) , Sub stream: D1/CIF/QCIF(1~25/30fps)  
 1/4/8/9/16  
 1 channel, RCA  
 1 channel, RCA  
 MD Zones: 396 (22 x 18)  
 Supports  
 Supports  
 iPhone, iPad, Android Phone  
 1 SATA port, up to 6TB  
 Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips  
 Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop  
 Time /Date, Alarm, MD and Exact Search (accurate to second)  
 Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom  
 USB Device / Network  
 1 HDMI, 1 VGA, 1 RS485, 2 USB Ports (1 USB 2.0 , 1 USB 3.0)  
 128 users  
 1 ~ 60 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec  
 1 RJ-45 Port (1000M)



\*Product casing and specifications are subject to change without prior notice

# CP- UVR-0801FM1

8 Ch. 4MP HDCVI DVR



## Feature

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

## Specification

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 2.42, CGI Conformant

DC12V/2A

<15W (Without HDD)

-10 ~+55°C / 10~90%RH

325mm x 255mm x 55mm

1.5KG(without HDD)