

CP- UVR-0804G1-HE

8 Ch. 720P HDCVI DVR

CP PLUS
CORAL



Main Features

- Up to 8 cameras with 1080p Realtime Preview
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- All Channels @720P
- Support 1 SATA HDD up to 4TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



CP- UVR-0804G1-HE

8 Ch. 720P HDCVI DVR



Feature

Processor
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Privacy Masking
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Alarm Input
 Alarm Output
 Hard Disk
 Smart Phone
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Interface Ports
 Record Interval
 Max User Account

Specification

Embedded processor
 Embedded LINUX
 Reuse audio input/output channel 1
 GUI
 8 channel, BNC
 1 HDMI, 1 VGA
 NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
 H.264 / G.711
 1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768, 800 × 600
 Main Stream: 1080P(1~12/15fps)/720P/960H/D1/HD1/2CIF/CIF(1~25/30fps), Extra Stream: CIF/QCIF(1~25/30fps)
 1/4/8/9
 4 rectangular zones (each camera)
 4 channel, RCA
 1 channel, RCA
 Supports
 Supports
 Supports
 8 channel
 3 channel
 1 SATA port, up to 4TB
 iPhone, iPad, Android, Windows Phone
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
 Manual, Schedule(Regular(Continuous), MD), Stop
 Time/Date, MD & Exact search (accurate to second)
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom
 USB Device/Internal SATA burner/Network
 1 HDMI, 1 VGA, 1 RS485, 2 USB2.0
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 128 users



CP- UVR-0804G1-HE

8 Ch. 720P HDCVI DVR

CP PLUS
CORAL

Feature

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

RJ-45 port (10/100M)

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP

DC12V/2A

10W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

325mm× 245mm× 45mm

1.5KG(without HDD)