



8 Ch. 1080P Cosmic HD DVR





Main Features

- Auto Adaptive HDCVI/AHD/TVI/CVBS signals
- Support upto 5MP IP Camera
- All channel 1080P Recording
- H.264Plus/ H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support Multi-brand network cameras
- Support 4 SATA HDD up to 8TB capacity for each disk,1 eSATA, 3 USB2.0
- Mobile Software: iCMOB, gCMOB
- CMS Software:KVMS, KVMS Pro



















CP- UVR-0804K4D-S

8 Ch. 1080P Cosmic HD DVR



Feature

Processor

IP Camera Input

Operating System

Two-way Talk

User Interface

Video Input Video Output

Video Standard Compression

Video Resolution

Video Recording

Video Display Split

Audio Input Audio Output

Motion Detection Video Loss

Camera Blank Alarm Input Alarm Output

Hard Disk Smart Phone

Trigger Events

Recording Mode Search Mode

Playback

Backup Mode Max User Account

Record Interval

Specification

Embedded processor

8+4 Channel, each channel up to 5MP

Embedded LINUX

1 channel Input, 1 channel Output, BNC

GUI

8 channel, BNC 1 HDMI, 1 VGA, 1 TV

Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)

H.264+/ H.264

1920×1080, 1280×1024, 1280×720, 1024×768

Main Stream: 1080P(1~12/15fps) / 1080N/720P/960H / D1(1~25/30fps), Extra Stream: D1/

CIF / QCIF(1~25/30fps)

1/4/8/9/16 4 channel, RCA 1 channel, RCA

Supports Supports Supports 8 channel 6 channel

4 SATA ports up to 8TB Capacity for each disk, 1 eSATA port

iPhone, iPad, Android Phone

Recording, PTZ, Tour, Alram Out, Video Push, Email, FTP, Spot, Buzzer & Screen tips

Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video

Loss, Tampering), Alarm, Stop

Time /Date, Alarm, MD and Exact Search (accurate to second), Smart search

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous

camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

USB Device/Network

128 users

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec











Feature

Interface Ports

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

1 HDMI, 1 VGA, 3 USB2.0, 1RS485, 1RS232

RJ-45 port (10/100M/1000M)

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS,

FTP, Alarm Server, P2P, IP Search, ONVIF 2.4.1, CGI Conformant

AC 100~240 V, 50/60 Hz

<30W(Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm×417mm×76mm

6KG(without HDD)



