

CP- UVR-0808G8D-H

8 Ch. 720P HDCVI DVR

CP PLUS
CORAL



Main Features

- Up to 8 cameras with 1080p Realtime Preview
- Support HDCVI / Analog / IP Video input
- H.264 dual-stream Video Compression
- HDMI / VGA / TV Simultaneous Video Output
- Support 8 SATA ports(8HDDs or 6HDDs 1CD/DVD-RW), up to 32TB, 1 eSATA up to 16TB, 4 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro

CP- UVR-0808G8D-H

8 Ch. 720P HDCVI DVR



Feature

Processor
Operating System
Two-way Talk
User Interface
Video Input
Video Output
Video Standard
Compression
Video Resolution
Video Recording
Video Display Split
Privacy Masking
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Hard Disk
Smart Phone
Trigger Events
Recording Mode
Search Mode

Playback

Backup Mode
Record Interval
Max User Account

Specification

Embedded processor
Embedded LINUX
1 channel Input, 1 channel Output, BNC
GUI
8 channel, BNC
1 HDMI, 1 VGA, 1 BNC
HDCVI: 1080P/720P HDCVI Camera, Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s), IP: 1080P/720P/D1/CIF IP Camera
H.264 / G.711
1920×1080, 1280×1024, 1280×720, 1024×768
Main Stream: 1080P(1~12/15fps)/720P/960H/D1/HD1/2CIF/CIF(1~25/30fps), Extra Stream: CIF/QCIF(1~25/30fps)
1/4/8/9
4 rectangular zones (each camera)
4 channel, RCA
1 channel, RCA
Supports
Supports
Supports
8 Channel
6 Channel
8 SATA ports(8HDDs or 6HDDs+1CD/DVD-RW), up to 32TB, 1 eSATA port up to 16TB
iPhone, iPad, Android, Windows Phone
Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
Manual, Schedule(Regular(Continuous), MD), Stop
Time/Date, MD & Exact search (accurate to second)

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

USB Device / Network
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
128 users

CP- UVR-0808G8D-H

8 Ch. 720P HDCVI DVR



Feature

Interface Ports

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

1 HDMI, 1 VGA, 1 RS485, 1 RS422, 1 RS232, 4USB2.0

2 RJ-45 port (10/100M/1000M)

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P

AC 100~240 V, 50/60 Hz

40W (Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm× 460mm× 68mm

6.5 Kg(without HDD)