

CP- UVR-0808K8D-S

8 Ch. 1080P Cosmic HD DVR





Main Features

- Auto Adaptive HDCVI/AHD/TVI/CVBS signals
- Support upto 5MP IP Camera
- All channel 1080P Recording
- H.264+/ H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support Multi-brand network cameras
- Support 8 SATA HDD up to 8TB Capacity for each disk,1 eSATA, 4 USB2.0
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



















CP- UVR-0808K8D-S

8 Ch. 1080P Cosmic HD DVR



Feature Specification

Processor Embedded processor

IP Camera Input 8+4 Channel, each channel up to 5MP

Operating System Embedded LINUX

Two-way Talk 1 channel Input, 1 channel Output, BNC

User Interface GUI

HD Camera Input 8 channel

Video Output 1 HDMI, 1 VGA, 1 TV
Video Standard Analog: NTSC/PAL
Compression H.264+/H.264

Video Resolution 1920×1080, 1280×1024, 1280×720, 1024×768

Video Recording

Main Stream: 1080P(1~12/15fps) / 1080N/720P/960H / D1(1~25/30fps), Extra Stream: D1/

 $CIF / QCIF(1{\sim}25/30 fps)$

Video Display Split 1/4/8/9/16 **Audio Input** 8 channel **Audio Output** 1 channel Motion Detection Supports Video Loss Supports Camera Blank Supports Alarm Input 8 channel Alarm Output 6 channel

Smart Phone iPhone, iPad, Android Phone

Hard Disk 8 SATA ports up to 8TB capacity for each disk, 1 eSATA port

Trigger Events Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Spot, Buzzer & Screen tips

Recording Mode Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video

Loss, Tampering), Alarm, Stop

Search Mode Time /Date, Alarm, MD and Exact Search (accurate to second), Smart search

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous

camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

Backup Mode USB Device/Network

Interface Ports 1 HDMI, 1 VGA, 1TV, 4 USB2.0, 1 RS485, 1RS232

Max User Account 128 users





CP- UVR-0808K8D-S

8 Ch. 1080P Cosmic HD DVR



Feature

Record Interval

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

2RJ-45 port (10/100M/1000M)

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS,

FTP, Alarm Server, P2P, IP Search, ONVIF 2.4.1, CGI Conformant

AC 100~240 V, 50/60 Hz

<35W(Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm×455mm×95mm

6.5KG(without HDD)



